

METHOD FOR CALIBRATING COLOR OF AN IMAGE
IN TRANSMISSION OF A DIGITAL IMAGE

5 BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a method for calibrating color of an image, such as a color photograph, in transmission of a digital image between a pair of computer image processing systems A, B.

2. Description of the Related Art

Along with the advances made in computer image processing and the advances made in digital data communications, it has become possible to send digital images from one location to another in a very short time regardless of the distance. In particular, the recent advances in Internet communications have made possible the convenient transmission and reception of digital images. These activities are now entering even our daily lives. Specifically, digital images are being transmitted through Internet communication systems from large numbers of unspecified points of transmission to organizations having specific specialized image processing (including value judging, image correction and processing, and printing) systems and are being processed to order in the specific specialized image processing systems. Further, specialized businesses having a plurality of computer image processing systems are using a combination of these systems for streamlining their work.

Such modern systems for transmission and reception of digital images, however, have only just been put together. The fact is that there are still problems which remain to be solved. One of the problems is the mismatch of the color of the image transmitted between a pair of computer image processing systems (brightness, contrast, chroma, and color balance, hereinafter referred to simply as "color").

In general, to read an image into a computer as digital data, the image is either read through a scanner or the image is captured by a digital camera and that digital data of the image recorded in the camera is read by connecting the camera to the computer. Whatever the case, it is impossible to avoid the reading function of the reading apparatus having an effect on the color of the image. Therefore, it is only natural that the color of the image read by the reading apparatus may not match the color of the digital image displayed on the monitor of the computer. Of course, further reading errors of color data are unavoidable in different reading apparatuses and are unique to each apparatus.

The extent of the color mismatch due to such unavoidable reasons is fixed within each system, so the problem becomes more complex between reading apparatuses in a pair of systems. On top of this, in the case of unspecified large numbers of systems, it may be said with no exaggeration that this problem has to be solved or else no further spread of image transmission systems can be expected.

SUMMARY OF THE INVENTION

To solve the above problem, the invention of the present application has as its object the provision of a rational method of calibration for adjusting the above-mentioned mismatch of color of an image when using a certain pair of computer image processing systems or a plurality of computer image processing systems in combination or between two computer image processing systems through a system for transmission or reception of digital images using a communication system such as an Internet communication system.

To solve this problem, the invention of the present application was developed based on the confirmation by experiment that the problem of mismatch of color of an image when transmitting an image between a pair of computer image processing systems comprised of

09749443 122800

5

10

25

35

The method for calibrating color of a color image in transmission between a pair of computer image processing systems A and B according to the present invention as mentioned above, comprises a first step of setting a correction value for applying to a color matching operation of either one of the computer image processing systems A and B, and a second step of operation of color matching of a digital image indicated in either one of the systems A and B to a color of an original image before said transmission of the color image, respectively.

The first step of setting a correction value is started from an advance preparation of a reference color image as a common standard color image Z for the systems A and B. Then the color image Z is transferred from the system A to the system B and a color matching operation is applied to a transferred digital image which is displayed on the monitor of the system B against the color image Z, so that a difference of color data (brightness, contrast, chroma, and color data) from an origin (zero point) displayed on the monitor of the system B, is detected, and the correction value is set based upon this detected data.

The color matching operation applied to a transmission of any color images from the system A to system B is carried out by the following second step operation, that is, the color matching operation applied to a digital image displayed on the monitor of the system B is carried out by adopting the above-mentioned correcting value.

The basic technical idea of the present invention can be successfully applied to the color matching operation between a digital image indicated in the monitor of the system A and a digital image
5 (corresponding to the above-mentioned digital image) indicated in the monitor of the system B, even though the transmission manner of the digital image is different from the above-mentioned explanation. Such effects of the present invention are hereinafter clarified by the
10 detailed explanation of several embodiments.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention may be more fully understood from the description of the preferred embodiments of the invention set forth below together with the accompanying
15 drawings, in which:

Fig. 1 is an explanatory view of an outline of the arrangement of equipment of computer image processing systems A and B in a typical embodiment of the basic aspect of the invention.

20 Fig. 2 is a flow chart indicating the action steps of the first embodiment of the present invention.

Fig. 3 is a view of an example of a reference color basic image used for correction of the color of an image in transmission of an image shown in Figs. 1 and 2.

25 Fig. 4 is a flow chart indicating the action steps of the second embodiment of the present invention.

Fig. 5 is a flow chart indicating the action steps of the third embodiment of the present invention.

30 Fig. 6 is a view of the image (line drawing) of an original photograph of a combination of fruit.

Fig. 7 is a view of the image (line drawing) of an original photograph of Mt. Bandai.

35 Fig. 8 is a view of the image of the original photograph of Mt. Bandai, indicating instructions for trimming.

Fig. 9 is a view of the expected image of Mt. Bandai indicating desired color balance between components of

003221 ETT64/60

picture.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Information transmission systems linking a pair of computer image processing systems A and B through a communications line have already been perfected. The ability to precisely transmit digital data through them is a well known fact. Further, it is well known that precise digital data can be transmitted in a similar fashion even when transmitting digital data between the two systems by an MO disc. Therefore, for convenience in explanation, the invention of the present application will be explained with reference to the case of use of an MO disc.

First, an embodiment showing the basic technical idea of the invention of the present application will be explained with reference to Fig. 1. As shown in Fig. 1, the basic invention will be explained with reference to the example of use of a computer image processing system using a Power Macintosh G3 as the computer 1, a Mitsubishi Diamond RD 21G as the monitor 2, an Epson Inkjet Printer 2000C as the printer 3, a Microtek Scan Maker 5 as the scanner 4, and an Olympus Turbo MO 640S as the MO drive 5 (hereinafter referred to as the "system A") and a computer image processing system using a Power Macintosh 9600/300 as the computer 6, a Sony FD Trinitron GPD-G500 as the monitor 7, an Epson Inkjet Printer 2000C as the printer 8, a Microtek Scan Master 4 as the scanner 9, and an Olympus Turbo MO 640S as the MO drive 10 (hereinafter referred to as the "system B") as the pair of computer image processing systems.

As shown in Fig. 1, a known RGB color image (Fig. 3) is prepared as a reference color image and a positive film of a photograph (Fig. 5) of fruit is prepared as the original image for transmission of images from the system A to the system B equipped with the above equipment.

As explained already, in the present invention, it is normal that the preparatory action for setting the

calibration value and the color matching operation applied to a digital image displayed on a monitor of either one of the systems A, B are independently carried out. In the Japanese patent application No. PH11-375423, which is the parent patent application from which present patent application claims convention priority, since the first embodiment was carried out with the systems A and B positioned very close together in the inventor's laboratory, the scanning of the original image X was carried out successively to that for the standard color image Z.

To clarify the characteristic feature of the present invention, the first embodiment was carried out in the above-mentioned normal way, and thereby an identical result of the experiment to the first embodiment explained in the Japanese patent application, was obtained.

The first embodiment is hereinafter explained with reference to the flow chart shown in Fig. 2.

As indicated in this flow chart, as the first action, the standard color image Z (RGB color image) shown in Fig. 3 was scanned by the scanner 4 of the system A, whereby digital data of the color image Z was stored in a memory of the computer 1, then this digital data was written on an MO disc by the MO driver 5 (step 1), and this digital data was transmitted to the system B, where the digital data was stored in a memory of the computer 6 of the system B, and a digital image Z_1 was displayed on the monitor 7 of the system B (step 2).

Next, a conventional color matching operation was applied to the digital image Z_1 of the system B by adjusting color data (brightness, contrast, chroma, color balance (R, G, B)) displayed on the monitor 7 whereby a digital image Z_2 being substantially identical to that of Z was displayed on the monitor 7, and then the deviation of color data from the origin (zero point) was read as the correction value α . This correction value was

brightness (-54), contract (-9), chroma (0), color was (R (-8), G (0), B (-6)) (step 3).

Like the standard color image Z, the original image X was scanned by the scanner 4 of the system A and the digital data of X was stored in the memory of the computer 1 of the system A, then this digital data was written on an MO disc by the MO drive 5 (step 4). Then this digital data was transmitted to the system B by MO, whereby a digital image X_1 was displayed on the monitor 7 of the system B (step 5).

Next, the color matching operation is applied to the digital image X_1 by adopting the above-mentioned correction value α whereby a digital image X_2 being substantially identical to X was displayed on the monitor 7 of the system B.

The second embodiment is an experiment successively applied to the experiment disclosed in the first embodiment, therefore the result of the additional experiment is only disclosed with reference to the flow chart shown in Fig. 4, as follows.

As shown in the flow chart of Fig. 4, as the additional first step action, the standard color image Z was scanned by the scanner 4 of the system A and the digital data thereof was stored in the memory of the computer 1 and digital image Z_3 was displayed on the monitor 2, then as the second additional step, the conventional color matching operation was applied to the digital image Z_3 .

Thereafter, as the third step action, deviation of color data from the origin (zero point) was read, as the step 3 of the first embodiment, and a correction value β which can be applied to the color-matching operation applied to a digital image displayed on the monitor 2 of the system A, which digital image is created by the identical successive operations to the successive operations to display the digital image Z_3 on the monitor

After the above-mentioned preparatory operation, as the fourth step, the printed picture of fruits (original image) X was scanned by the scanner 4 of the system A and the digital image X_3 was displayed on the monitor 2 of the system A. Then the color matching operation was applied to the digital image X_3 by adopting the above-mentioned correction value β so that a modified digital image X_4 , having substantially identical color to the original image, was displayed on the monitor 2.

As is clear from the flow chart shown in Fig. 5, it is necessary to find a correction value γ for the color matching operation applied to the digital image X_5 displayed on the monitor 7 of the system B whereby a modified digital X_6 is displayed on the monitor 7 of the system B.

Then the conventional color matching operation is applied to the digital image Z_5 , whereby a digital image

manual, the explanation of this action in the action program is omitted.

In the condition that the action program titled "Action program 1" is installed in the memory of the computer 6 of the system B, the fifth step is carried out as follows. As disclosed in the explanation of the first embodiment, the digital data of X is transmitted to the system B by the step action 2 so that the digital image X_1 is displayed on the monitor 7 of the system B. The computer 6 is then operated to apply the above-mentioned action program titled "Action program 1" to modify the color of the digital image X_1 , and as a result of this calibration action, a digital image X_2 having a color substantially identical to that of the color of the original image X (printed picture of Mt. Bandai in this case) was indicated on the display 7 of the system B.

Since it is clear from the result of the fourth embodiment that the working efficiency of the color matching operation is much higher than that of the manual color matching operation disclosed by the first embodiment wherein matching of each color data such as brightness, contrast, chroma, and color balance is successively carried out manually. Therefore, a very effective result of this type of color matching operation can be expected in the case of a continuous business relationship of digital image transmission between the system A and system B. And it is further noted that a so-called batch operation can be successfully apply to a group of plural digital images transmitted from the system A.

The next embodiment concerns an application of the present invention related to a network system in the business of photography formed by a main shop (hereinafter referred as the system B), having sufficient power of carrying out the computer image processing process, and at least one subsidiary shop (hereinafter

003227 0444280

referred to as the system A) without such power as the system B.

In this embodiment, the experiment was planned to carried out as follows: that is, the system A receives an order from a customer M to make an enlarged printed picture of Mt. Bandai from an original printed picture X with reference to the customer's instruction note. Then, the system A scans this printed picture X by their computer system and the scanned digital data is transmitted to the system B together with the digital data of the instruction note, so that the digital image X_1 and any other images of the instruction note are displayed on the monitor 7 of the system B, then a color matching operation is applied to this digital image X_1 so that a modified digital image X_2 having a color being substantially coincident with the color of the printed picture X is displayed on this display 7.

Thereafter, this digital image X_2 is processed with reference to the contents of the instruction indicated on display of this system B. This process is carried out by using a known technique to change the composition by trimming and adjusting the color balance (brightness, contrast, chroma, and color balance) of the components of the digital image X_2 . As a result of such processing, a final image X_3 is created on the monitor 7.

The next step action is the preparatory action applied to the digital image X_3 before transmitting the image to the system A. It was recognized from the experiments of the above-mentioned embodiments that the correction value Σ applied to the color-matching operation applied to the case of transmission from the system B to the system A is identical to $(-\Sigma)$ wherein Σ is the correction value applied to the case of transmitting a digital image from the system A to the system B, to satisfy the condition of color matching the corresponding digital images displayed on the respective

monitors of these systems A and B. Therefore the color modification is applied to the digital image X , by adopting the correction value δ , that is a correction value (brightness (+15), contrast (+6), chroma (0), color balance (R (+7), G (0), B (+5)), whereby a color-modified digital image X_8 can be displayed on the monitor 7 of the system B. Thereafter, the digital image X_8 is transmitted to the system A by an MO disc. Accordingly, a digital image X_9 having identical composition and color to the digital image X_7 can be displayed on the monitor 2 of the system A.

The first action of the experiment of the fifth embodiment was started by making a reference note Q based upon the above-mentioned instruction. Thereafter, the printed picture X of Mt. Bandai and the reference note were scanned by the scanner 2 of the system A, then the scanned digital data of these materials were transmitted to the system B by MO disc whereby a digital image X_1 and a digital image Q_1 of the reference note Q were displayed on the monitor 7 of the system B.

Next, the color matching operation was applied to the digital images X_1 and Q_1 by adopting a correction value being identical to the correction value α selected in the experiment of the first embodiment, whereby a digital image X_2 having substantially identical color to the original picture X was displayed on the monitor 7 of the system B, while the digital image Q_2 indicating color balance of the background sky (11), top portion of Mt. Bandai (12), thin cloud portion (13) and mountain range (14, 15, 16 and 17) was also clearly displayed on the monitor 7.

The third step action was applied to create a new digital image X , based upon the instruction indicated in the digital image of the above-mentioned reference note. That is, digital data processing was carried out by operating the computer 6 of the system B based upon the

reference note (digital image Q_2) so that digital image X_7 was displayed on the monitor 7 of the system B.

The fourth step action, which is the preparatory action applied to the digital image X_7 , before
5 transmission to the system A, was carried out by adopting the correction value γ mentioned above, that is, a color modification operation was applied to the digital image X_7 , by adopting the above-mentioned correction value γ whereby a color-modified digital image X_8 was displayed
10 on the monitor 7 of the system B. Thereafter, the digital image X_8 was transmitted from the system B to the system A by MO disc, and as the result of this transmission of the digital image X_8 , a digital image X_9 was displayed on the monitor 2 of the system 2.

15 As already explained in the introduction part of the present specification, the color mismatch problem in the digital image transmission between the system A and system B is mainly caused by the characteristics of the function of the equipments making up these systems.
20 Therefore, the correction value for adopting the color matching operation according to the present invention could be constant, unless the basic function of the equipment is changed. However, in the present invention, since the color matching operation for finding a
25 correction value is carried out on the basis of manual observation, it is impossible to prevent deviation of observed color data, even if such a deviation is small. The influence of the environment during the color matching observation to find a correction value must also
30 be considered. Accordingly, the following method to raise the level of accuracy of the correction value is recommended. (1) The environment during the process to find a correction value is desired to maintained in a highly constant condition. (2) The correction value
35 should be settled several times and an average of the correction values should be set as a standard correction

003221 544460

value. If such an action is carried out by several persons, a more reliable result can be expected.

According to the experience of the applicant, it is also helpful to increase the accuracy of the correction value by the result of the color matching operation applied to several cases of digital transmission between two systems located in an identical working place.

EFFECT OF THE INVENTION

As explained above, the previously unavoidable problem of mismatch between the color (brightness, contrast, chroma, and color balance) of images in transmission of images between a pair of computer image processing systems can be eliminated by an extremely simple operation. Therefore, in the case of maintaining a continuous business relation between the system A and the system B, once the above-mentioned correction value is settled for applying the color matching operation, the color matching operation can be carried out very effectively, until the basic condition that can be affect the correction value is changed. Due to such an advantage attained by the present invention, it is expected to contribute a great deal to business engaged in image processing by a plurality of computer image processing systems and to development of image processing by specialized business using communication by, for example, the Internet.

While the invention has been described by reference to specific embodiments chosen for purposes of illustration, it should be apparent that numerous modifications could be made thereto by those skilled in the art without departing from the basic concept and scope of the invention.